



SAFETY DATA SHEET

FAST TAK CONTACT ADHESIVE

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME: FAST TAK CONTACT ADHESIVE

PART No.: 91770

SUPPLIER: BOSTIK FINDLEY LIMITED
COMMON ROAD
STAFFORD. ST16 3EH
STAFFORDSHIRE
Tel: +44 1785 272727
Fax: +44 1785 257236

EMERGENCY TELEPHONES: +44 1785 255141 +44 1785 272650

2. COMPOSITION/INFORMATION ON INGREDIENTS

NAME	EINECS Nr.:	CLASSIFICATION	CONTENT
BUTANE/PROPANE PROPELLANT		Fx R-12	10-30 %
PETROLEUM DISTILLATE (<0.1% BENZENE)			10-30 %
92062-15-2	295-529-9	Xn ,F ,N R-11, 38, 51/53, 65, 67 Carc2	
ACETONE			10-30 %
67-64-1	200-662-2	Xi ,F R-11, 36, 66, 67	

The Full Text for all R-Phrases are Displayed in Section 16

3. HAZARDS IDENTIFICATION

Extremely flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

4. FIRST AID MEASURES

INHALATION: Remove victim immediately from source of exposure. Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION: DO NOT induce vomiting. Get medical attention immediately.

SKIN: Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYES: Rinse the eye with water immediately. Continue to rinse for at least 15 minutes and get medical attention.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use: Powder. Foam.

SPECIAL FIRE FIGHTING PROCEDURES: Use water SPRAY only to cool containers! Do not put water on leaked material. If possible, fight fire from protected position.

UNUSUAL FIRE & EXPLOSION HAZARDS: Aerosol cans may explode in fires.

HAZARDOUS COMBUSTION PRODUCTS: Toxic gases/vapors/fumes of: Carbon dioxide (CO₂). Carbon monoxide (CO).

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTION IN SPILL: Avoid skin and eye contact. Ensure adequate ventilation. Wear personal protective equipment. Wear self contained breathing apparatus.

PRECAUTIONS TO PROTECT ENVIRONMENT: Prevent entry into drains and water courses.

SPILL CLEANUP METHODS: Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. If leakage cannot be stopped, evacuate area. Absorb onto sand, earth or absorbent granules. Pick up with non-sparking tools and place into metal containers with sealable lids. Mark containers with details of hazards and store in designated area ready for disposal.

7. HANDLING AND STORAGE

USAGE PRECAUTIONS: Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS: Aerosol cans: Must not be exposed for direct sunlight or temperatures above 50°C.

STORAGE CRITERIA: Flammable compressed gas storage.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

INGREDIENT NAME:	CAS No.:	STD	LT EXP 8 Hrs	ST EXP 15 Min
ACETONE	67-64-1	OES	500 ppm	1500 ppm

PROTECTIVE EQUIPMENT:



PROCESS CONDITIONS: Use engineering controls to reduce air contamination to permissible exposure level.

VENTILATION: Provide adequate general and local exhaust ventilation.

RESPIRATORS: If ventilation is insufficient, suitable respiratory protection must be provided.

PROTECTIVE GLOVES: Protective gloves should be used if there is a risk of direct contact or splash. Use

	protective gloves made of: Nitrile.
EYE PROTECTION:	Use eye protection.
OTHER PROTECTION:	Wear suitable protective clothing as protection against splashing or contamination.
HYGIENIC WORK PRACTICES:	DO NOT SMOKE IN WORK AREA!

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Aerosol.		
COLOUR:	Colourless.		
SOLUBILITY DESCRIPTION:	Slightly soluble in water.		
FLASH POINT (°C):	- 30	Method:	Not noted.

10. STABILITY AND REACTIVITY

STABILITY:	Avoid: Heat, sparks, flames.
CONDITIONS TO AVOID:	Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

11. TOXICOLOGICAL INFORMATION

INHALATION:	Solvent vapours are hazardous and may cause nausea, sickness and headaches. Prolonged inhalation of high concentrations may damage respiratory system. May cause sensitisation by inhalation.
INGESTION:	Pneumonia may be the result if vomited material containing solvents reaches the lungs.
SKIN:	Irritating to skin.
EYES:	Irritation, burning, lacrimation, blurred vision after liquid splash.
ROUTE OF ENTRY:	Inhalation.

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION:	Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.
--------------------------------	--

13. DISPOSAL CONSIDERATIONS

GENERAL/CLEANING:	This material is classified as special waste as defined by Special Waste Regulations 1996 and must be disposed of by an authorised contractor
DISPOSAL METHODS:	Empty containers must not be burned because of explosion hazard. Dispose of in accordance with Local Authority requirements.

14. TRANSPORT INFORMATION

LABEL FOR CONVEYANCE:



UN No. ROAD:	1950
UK ROAD TRANSPORT CLASS:	2.1
UK ROAD PACK GR.:	Not Applicable
ADR CLASS No.:	2.1
ADR CLASS:	Division 2.1: Flammable gases.
ADR PACK GR.	Not Applicable
ADR LABEL No.:	2.1
CEFIC TEC(R) No.:	20G5F
PROPER SHIPPING NAME I:	AEROSOLS
RID CLASS No.:	2.1
RID PACK GR.	Not Applicable
UN No. SEA:	1950
IMDG CLASS:	2.1
IMDG PACK GR.:	Not Applicable
EmS No.:	2-13
MFAG TABLE No.:	See Guide
MARINE POLLUTANT:	No.
UN No., AIR:	1950
ICAO CLASS:	2.1
AIR PACK GR.:	Not Applicable

15. REGULATORY INFORMATION

LABEL FOR SUPPLY:



CONTAINS

PETROLEUM DISTILLATE (<0.1% BENZENE)

RISK PHRASES:	R-12 Extremely flammable. R-52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R-65 Harmful: may cause lung damage if swallowed. R-67 Vapours may cause drowsiness and dizziness.
SAFETY PHRASES:	S-16 Keep away from sources of ignition - No Smoking. S-23 Do not breathe gas/fumes/vapour/spray. S-24/25 Avoid contact with skin and eyes. S-36/37/39 Wear suitable protective clothing, gloves and eye/face protection. S-51 Use only in well-ventilated areas. S-60 This material and its container must be disposed of as hazardous waste. S-9 Keep container in a well-ventilated place.

16. OTHER INFORMATION

USER NOTES:	This product should be used as directed by Bostik Findley Ltd. For further information consult the product data sheet or contact Technical Services.
INFORMATION SOURCES:	This safety data sheet was compiled using current safety information supplied by distributor of raw materials.
REVISION COMMENTS:	This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Bostik Findley Limited.
ISSUED BY:	Approved EC
REVISION DATE:	Jan 2003
REV. No./REPL. SDS GENERATED:	IMP-1
SDS No.:	1
DATE:	Jan 2003
PRINTING DATE:	2003-03-27
R-PHRASES (Full Text):	R-11 Highly flammable. R-36 Irritating to eyes. R-66 Repeated exposure may cause skin dryness or cracking. R-67 Vapours may cause drowsiness and dizziness. R-12 Extremely flammable. R-38 Irritating to skin. R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R-65 Harmful: may cause lung damage if swallowed.