

**EVERBUILD WOODSTAIN** 

Page: 1

Compilation date: 21/11/2011

Revision No: 1

## Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: EVERBUILD WOODSTAIN

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

## 1.3. Details of the supplier of the safety data sheet

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

**LEEDS** 

WEST YORKSHIRE

LS9OSW ENGLAND

Tel: 0044 113 240 3456

Fax: 0044 113 240 0024

Email: pault@everbuild.co.uk

## 1.4. Emergency telephone number

Emergency tel: 0044 113 240 3456 (office hours only)

## **Section 2: Hazards identification**

## 2.1. Classification of the substance or mixture

Classification under CHIP: -: R52/53

Most important adverse effects: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

#### 2.2. Label elements

Label elements under CHIP:

Hazard symbols: Symbol not required.

Risk phrases: R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Safety phrases: S29: Do not empty into drains.

Precautionary phrases: Contains preservative based on: biphenyl-2-ol and 2-methyl-2h-isothiazol-3-one. May

produce an allergic reaction.

## 2.3. Other hazards

**PBT:** This substance is not identified as a PBT substance.

## **EVERBUILD WOODSTAIN**

Page: 2

## Section 3: Composition/information on ingredients

## 3.2. Mixtures

## **Hazardous ingredients:**

PRESERVATIVE BASED ON: BIPHENYL-2-OL AND 2-METHYL-2H-ISOTHIAZOL-3-ONE

EINECS	CAS	CHIP Classification	CLP Classification	Percent		
-	-	Xi: R36/38; Sens.: R43; N: R50	-	<1%		
2-(2-BUTOXYETHOXY)ETHANOL						
203-961-6	112-34-5	Xi: R36	-	1-10%		
DIURON (ISO)						
206-354-4	330-54-1	Xn: R40; Xn: R22; Xn: R48/22; N: R50/53	-	<1%		

#### Section 4: First aid measures

#### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water. **Eye contact:** Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

## 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

### Section 5: Fire-fighting measures

# 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

## 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

## **EVERBUILD WOODSTAIN**

Page: 3

#### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers

leak-side up to prevent the escape of liquid. Mark out the contaminated area with signs

and prevent access to unauthorised personnel.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

# 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

## Section 7: Handling and storage

#### 7.1. Precautions for safe handling

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage

room must be impermeable to prevent the escape of liquids.

# 7.3. Specific end use(s)

Specific end use(s): No data available.

#### Section 8: Exposure controls/personal protection

## 8.1. Control parameters

# Hazardous ingredients:

# 2-(2-BUTOXYETHOXY)ETHANOL

## Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	67.5 mg/m3	101.2 mg/m3	-	-

#### **DIURON (ISO)**

UK	10 mg/m3	-	-	-
----	----------	---	---	---

# 8.2. Exposure controls

Engineering measures: The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.Eye protection: Safety glasses.

## **EVERBUILD WOODSTAIN**

Page: 4

Skin protection: Protective clothing.

# Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State: Liquid Colour: Various

Odour: Barely perceptible odour

Solubility in water: Miscible

Boiling point/range°C: ~100

pH: Approx. 7

#### 9.2. Other information

Other information: Not applicable.

Viscosity: Viscous

#### Section 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

Flash point°C: >93

#### 10.4. Conditions to avoid

Conditions to avoid: Heat.

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

## 11.1. Information on toxicological effects

Toxicity values: Not applicable.

## Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

## **EVERBUILD WOODSTAIN**

Page: 5

## Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

#### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

## **Section 14: Transport information**

**Transport class:** This product does not require a classification for transport.

## **Section 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

# **Section 16: Other information**

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: R22: Harmful if swallowed.

R36/38: Irritating to eyes and skin.

## **EVERBUILD WOODSTAIN**

Page: 6

R36: Irritating to eyes.

R40: Limited evidence of a carcinogenic effect.

R43: May cause sensitisation by skin contact.

R48/22: Harmful: danger of serious damage to health by prolonged exposure if

swallowed.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R50: Very toxic to aquatic organisms.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.