

SAFETY DATA SHEET

AC95 ACOUSTIC INTUMESCENT SEALANT AND ADHESIVE

Page 1 Issued: 15/11/2004 Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: AC95 ACOUSTIC INTUMESCENT SEALANT AND ADHESIVE

Product code: AC95

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE LS9OSW ENGLAND Tel: 0044 113 240 3456 Fax: 0044 113 240 0024 Emergency tel: 0044 113 240 3456 (office hours only) Email: pault@everbuild.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: No significant hazard.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Contains: Contains a plasticised water based acrylic emulsion with dense fillers, very minor amounts of

white spirits (ca. 1%), dispersants, bocides, and acrylic associate thickeners.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water. Eye contact: Bathe the eye with running water for 15 minutes. Ingestion: Wash out mouth with water.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Exposure hazards: In combustion emits toxic fumes. Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

SAFETY DATA SHEET

AC95 ACOUSTIC INTUMESCENT SEALANT AND ADHESIVE

Page 2

Hand protection: Protective gloves.
Eye protection: Safety glasses. Ensure eye bath is to hand.
Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

6. ACCIDENTAL RELEASE MEASURES

State:	Paste
Colour:	White
Odour:	Barely perceptible odour
Evaporation rate:	Slow
Oxidising:	Non-oxidising (by EC criteria)
Solubility in water:	Miscible
Viscosity:	Viscous
Viscosity value:	100-200
Viscosity test method:	x 1000 cps - Brookfield HBDV2+, spindle S70, 10rpm @ 20°C
Boiling point/range°C:	100
Flammability limits %: lower:	N/A
upper:	N/A
Autoflammability°C:	N/D
Vapour pressure:	as water
Relative density:	1.57
pH:	8.5-9.9

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

SAFETY DATA SHEET

AC95 ACOUSTIC INTUMESCENT SEALANT AND ADHESIVE

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

Other adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Dispose of according to local or national legislation

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: Not Classified.

IMDG / IMO

UN no: Not Classified.

IATA / ICAO

UN no: Not Classified.

15. REGULATORY INFORMATION

Hazard symbols: No significant hazard.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. Page 3