

The double-blade non-porous rubber design of this squeegee is effective in removing water from all types of floors; tiles, epoxy, cement. The revolving neck and 400mm length blade is useful for small or cluttered production areas. It reaches comfortably unerneath low lying equipment. Replacement Squeegee Blade: Series 7732.

Technical data

Gtin-13 Number	5705020772245
GTIN-14 Number	15705020772242
Commodity Code	96039099
Suitable for Food Contact (EU 1935/2004), DoC	Yes
FDA compliant raw material (CFR 21)	Yes
Produced according to EU Regulation 2023/2006/EC of Good Manufacturing Practice	Yes
Use of Phthalates (e.g. Bisphenol A)	No
Material	Polypropylene, TPE Rubber
Colour	Red
Box Quantity	10 Pcs.
Quantity per Pallet (80 x 120 x 200 cm)	480 Pcs
Box Length	410 mm
Box Width	290 mm
Box Height	210 mm
Length	405 mm
Width	100 mm
Height	75 mm
Gross Weight	0.337 kg
Net Weight	0.304 kg
Cubik metre	0.003038 M
Country of origin	Denmark
Max cleaning temperature (Autoclave)	121 °Celsius
Max. cleaning temperature (Dishwasher)	93 °Celsius
Max. usage temperature (for food contact)	50 °Celsius
Max usage temperature (non food contact)	100 °Celsius
Min. usage temperature	-20 °Celsius
Min. pH-value in usage concentration	2
Max. pH-value in Usage Concentration	10.5

New equipment should be cleaned, disinfected, sterilised and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.