Item number: 2973Q3

Aluminium Telescopic waterfed Handle w/metal coupling, 1600 - 2780 mm, Ø32 mm, Blue



This waterfed extendable handle allows reach of approximately 4.3m. Water travels from a hose through an inner tube and exits a waterfed brush. Example: 7067, 7043. It can also be used with 7716 to remove condensation from overhead pipes or ceilings. The quick connect coupling feature allows for easy attachment of a hose or bottle.

## **Technical data**

GTIN-14 Number  Commodity Code  FDA compliant raw material (CFR 21)  Produced according to EU Regulation 2023/2006/EC of Good Manufacturing Practice  Use of Phthalates (e.g. Bisphenol A)  Max. bars pressure  Material  Anodis	15705022973302 76042910 Yes Yes No 6 sed Aluminium, Polypropylene
FDA compliant raw material (CFR 21)  Produced according to EU Regulation 2023/2006/EC of Good Manufacturing Practice  Use of Phthalates (e.g. Bisphenol A)  Max. bars pressure	Yes Yes No
Produced according to EU Regulation 2023/2006/EC of Good Manufacturing Practice  Use of Phthalates (e.g. Bisphenol A)  Max. bars pressure	Yes No
Manufacturing Practice  Use of Phthalates (e.g. Bisphenol A)  Max. bars pressure	No 6
Max. bars pressure	6
<u> </u>	
Material Anodis	sed Aluminium, Polypropylene
Material	
Colour	Blue
Box Quantity	5 Pcs.
Quantity per Pallet (80 x 120 x 200 cm)	480 Pcs
Box Length	1755 mm
Box Width	170 mm
Box Height	75 mm
Product Diameter	32 mm
Length	1600 mm
Width	32 mm
Height	32 mm
Max. Length	2780 mm
Gross Weight	1.095 kg
Net Weight	1.012 kg
Cubik metre	0.001638 M
Country of origin	Denmark
Max cleaning temperature (Autoclave)	121 °Celsius
Min. usage temperature	-20 °Celsius
Min. pH-value in usage concentration	2
Max. pH-value in Usage Concentration	8

New equipment should be cleaned, disinfected, sterilised and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.