

# HOOK-UP WIRE



MIL-W-81044/12

CROSS-LINKED  
POLYALKELENE PVF

**Description:**

Stranded, Tinned Copper, Color Coded Irradiation Cross-Linked Extruded Polyalkelene with Clear Irradiation Cross-Linked Extruded Polyvinylidene Fluoride (PVF) Jacket.

**Characteristics:**

Temperature Rating: 150°C  
Voltage Rating: 600V

WEICO NO.	MILITARY NO.	CONDUCTOR		NOM. O.D. (IN)
		SIZE	STRAND	
9897	M81044/12-26-X	26	19/38	.036
9896	M81044/12-24-X	24	19/36	.042
9895	M81044/12-22-X	22	19/34	.049
9894	M81044/12-20-X	20	19/32	.057
9893	M81044/12-18-X	18	19/30	.067
9892	M81044/12-16-X	16	19/29	.075
9891	M81044/12-14-X	14	19/27	.093
9890	M81044/12-12-X	12	37/28	.112

**COLORS:**

**0** - Black, **1** - Brown, **2** - Red

**3** - Orange, **4** - Yellow, **5** - Green

**6** - Blue, **7** - Violet, **8** - Gray, **9** - White

X Denotes 0 - 9 color coding

**STRIPES:**

Any of the above colors are available in any combination of stripes up to a maximum of three stripes.

**Standard Put-Ups: 100 ft., 1000 ft.**