

TECHNICAL DATA SHEET

Product identifier: Consumables.com[™] Cowtail Tape, 24mm x 50m

Other means of identification: 130-5316

Details of the supplier of the Technical Data Sheet

Supplier :

Address: Consumables Solutions Limited
1000 Lakeside
North Harbour
Hampshire
PO6 3EN

Telephone: 03300 888 000
Fax: +0844 893 6540
E-mail: sales@consumables.com
Web Site: www.consumables.com

CHARACTERISTIC:

This Duct tape is designed to fix insulating covers such as panels or pipes, but also used for packaging and emergencies. Its resistance to breaking loads allows it to resist under conditions of high tension making it a "universal duct tape" in both professional contexts and for small domestic repairs.

Strengths:

- High tensile strength
- Adaptable to irregular surfaces
- High adhesion
- No residue
- Precise tear
- Removal without breaking



CHARACTERISTICS	UNITS	STD. VALUES	TOLERANCE	TEST METHOD
Total Weight	g/m ²	155	± 10%	ISO 536
Total Thickness	µm	175	± 10%	AFERA 5006
MD tensile strength	N/cm	> 32		AFERA 5004
MD elongation at break	%	> 10		AFERA 5004
Adhesion to steel plate	N/cm	> 6		AFERA 5001
Rolling ball tack	cm	< 0.5		PSTC 6

Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. All information has to be intended as generic advise for the use of products. Users have to verify the suitability of each tape in actual application under specific conditions.

AVAILABLE COLOURS:

- Black
- Silver
- White
- Beige
- Black
- Blue
- Brown
- Green
- Hi-Vis Yellow
- Orange
- Red

AVAILABLE SIZES:

- 24mm x 50m

NOTES:

Make sure the surface you wish to place the tape on is cleaned, dried and free from oil and dust.

It is suggested not to apply the tape with temperatures lower than 10°C.

With a storage temperature lower than 10°C, it is always suggested temperature reconditioning of the tape at room temperature (15°C - 25 ° C) before its use.

The information on this Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law).

The information may not be valid for any use not referred to in this Date Sheet or use of the product in combination with other materials.

For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.