

STICK 2 SPRAY CONTACT ADHESIVE

Colour	Product Code	Pack Size	Box Qty
Beige	CONSPRAY5	500ml	12

Product Description

STICK 2 SPRAY CONTACT ADHESIVE is a sprayable glue which bonds to most common materials including wood, concrete, stone, tiles, rubber foam, metals, rigid plastics, polyethylene, canvas, fabrics, cardboard, paper and cork. Ideal for securing most carpets/floor coverings, the product is suitable for internal and external use giving excellent permanent or temporary adhesion, depending on method of application.

Benefits

- Good adhesion - fast rate of tack development.
- Ease of use - no messy spreading/clean up
- Time saving- easier and quicker than most trowel/spreader applied adhesives.
- Foaming formula - gives low soak in into most substrates.
- Halogen and CFC Free.

Areas For Use

- Subfloors - eliminates the need for gripper rods
- Most joinery applications. Bonds all woods /composite board etc.
- Fixing most common laminate materials*
- Bonding metals to most surfaces.
- Bonds rubber, most plastics and leather
- As a general purpose household/hobby adhesive

Limitations

- Do not use on soft (plasticised) PVC.
- Do not use on polystyrene. Use EVERBUILD GUN A NAIL
- Do not use on cellulose painted surfaces
- Do not use on bitumen or tar leaching products.
- Medium strength adhesive - do not use on heavy/large/thick areas of laminate - Use STICK 2 ALL PURPOSE CONTACT ADHESIVE.

Surface Preparation

The surfaces to be glued should be clean and free from dust, grease and other contaminants. Materials should be stored in a warm environment prior to bonding to avoid chilling of the glue line, which leads to extended setting times.

Application

Shake the can well before use.

Select the fan width by turning the nozzle to the desired position. Spray adhesive from 6-8 inches away onto one or both surfaces; depending on the type of surface/strength of bond required. The surfaces to be glued should be clean and free from dust, grease and other contaminants. Shake well before use. Select fan width by turning to desired setting. Spray adhesive from 6 to 8 inches (15 to 20 cms approx.) away onto one or both surfaces, depending on type of strength of bond required.

STRONG BONDING

Apply 1-3 coats (depending on strength required) to both surfaces. Allow solvent to evaporate (30 seconds) and press surfaces together from centre outwards.

TEMPORARY REPOSITIONABLE BONDING:

Spray on one surface only and allow to dry for 2-3 minutes before bonding. Excess adhesive can be removed with STICK 2 CONTACT ADHESIVE THINNER AND CLEANER. To prevent spray nozzle from blocking, at the end of each day, turn can upside down and press nozzle until spray is clear of adhesive.

Excess adhesive can be removed using EVERBUILD GUN FOAM CLEANER. To prevent spray nozzle from blocking,; at the end of each use, turn can upside down and press nozzle until spray is clear of adhesive.

The newly bonded materials should not be subjected to extreme temperature changes for 3 to 4 days after bonding. Avoid further fabrication until the adhesive has fully cured.

Specific Data

Colour	Star
Base	Synthetic rubber/resin
Solids	10 – 20%
Viscosity	Low
Coverage	120 – 250ml per M ²
Tack Life	2 – 5 mins
Flash Point	-40°C
Cleaner	Everbuild Gun Foam Cleaner

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store in original unopened containers between 4 and 25°C. Store as flammable liquid.

Shelf Life

Twelve months from date of manufacture in original unopened containers.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.