

The REON™ face shield provides the wearer with ‘Class A’ face protection. High energy impact resistance to EN 166 ‘Level A’ means that the face shield protects against impacts up to 190m/s (425mph). REON is also top of the class for comfort and vision clarity.

SPECIAL FEATURES

- ✓ Ratchet adjustment allows for a secure fit to a range of head sizes
- ✓ Padded headband for a comfortable fit
- ✓ Adjustable pivot for wearer to select optimum angle
- ✓ Fitted chinguard
- ✓ Clear polycarbonate lens with anti-fog coating
- ✓ Level A impact resistance – the highest attainable level under EN 166
- ✓ Frameless design for a wide, unrestricted field of vision
- ✓ Simple, cost-efficient visor replacement system
- ✓ Protects against splashes of molten metal



VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
VISOR AND CHINGUARD	RLY00351	2C-1.2 e 1AT9 CE	N/A	Impacts, UV radiations, molten metal splash	Anti-fog
BROWGUARD	RLY00352	N/A	e EN 166 39AT CE		

See overleaf for this product's technical specification

GENERAL SPECIFICATION

LENS BASE	N/A
WEIGHT	360g

PACKAGING

Individually contained in a polythene bag

PER CARTON	50
------------	----

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS	Polycarbonate	Wide vision, high impact
HEADBAND	Nylon	Lightweight & positive ratchet fitting
HINGE	Metal	Increased strength


LENS MARKINGS

LENS FILTER TYPE:

2C UV

SCALE NUMBER (SHADE):

1.2 Clear or Amber

 Identity of the manufacturer

OPTICAL CLASS:


1 High optical quality

MECHANICAL STRENGTH:

- A High energy impact, resists a 6mm, 0.86 ball at 190m/s
- T Protection against high-speed particles at extreme temperatures
- 9 Molten metal splash

 Certification mark

FRAME MARKINGS

 Identity of the manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

FIELDS OF USE

- 3 Liquid droplets or splashes
- 9 Molten metal and hot solids

MECHANICAL STRENGTH:

- A High energy impact, resists a 6mm, 0.86g ball at 190m/s
- T Protection against high-speed particles at extreme temperatures

 Certification mark

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: A pitted, scratched or damaged visor or frame must be replaced.

STORAGE: All products must be stored in a dry and clean environment.

PART OF THE GLOBUS GROUP

Based on a substantial heritage of successfully protecting hands, Globus has grown to become one of the world leaders in worker safety, leading the way in technical innovation to provide a range of products that have set the standard for safety, productivity and wearer acceptance.

This focus on creating cutting edge personal protection solutions has now extended to eye and face protection with Riley; a new collection of high performance protective eyewear products engineered with innovation and ingenuity, designed for optimum comfort and styled for safe working.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

www.riley-eyewear.com

E: info@riley-eyewear.com

T: +44 (0)161 877 4747

F: +44(0)161 877 4746

Globus (Shetland) Ltd, 14 Central Park, Mosley Road, Manchester, M17 1NY, UNITED KINGDOM

