LPHA FLOW AMF-2V

P2 DISPOSABLE RESPIRATOR



The Alpha FLOW Series has been designed to improve comfort and performance whilst maintaining a secure fit. Colour coding the range makes identification simple and easy when varying levels of protection may be required.

FEATURES

- Large surface area ensures very low breathing resistance
- New large exhalation valve which reduces heat build-up and improves wearer comfort
- Colour coded alphamesh shell for ease of identification
- Adjustable headstrap allows for a secure and comfortable fit
- Metal-free suitable for food industry applications
- Preformed nosebridge eliminates the need for regular adjustment
- Compatible with a wide range of safety eyewear
- Soft flexible mesh maintains it's shape and will not collapse during use
- Conforms to EN 149: 2001 + A1: 2009 FFP2 NR



PREFORMED NOSEBRIDGE

Ensures excellent fit without the need to keep adjusting while wearing

NEW LARGE EXHALATION VALVE Reduces heat and moisture build-up

NEW MESH DESIGN Lightweight, flexible and will not collapse during use







ORDERING INFORMATION

Part Number: AMF-2V

Packaging: 10 singles per box

20 boxes per case

Certification: EN149: 2001 + A1: 2009

FFP2 NR

SUITABLE APPLICATIONS

Recommended applications include:

- Agriculture
- Construction
- Food Processing
- Laboratories
- Metalworking
- Pharmaceutical
- Powdered Chemicals
- Ship Building/Repair
- Woodworking Industry



LPHA FLOW AMF-2V





TECHNICAL SPECIFICATIONS

MATERIALS

| COMPONENT | MATERIAL |
|-----------------------------------|----------------------------|
| Mesh Shell: | Polypropylene |
| Filter Outer Layer: | Polypropylene |
| Filter Inner Layer: | Polypropylene |
| Filter Internal Media: | Melt-Blown [Polypropylene] |
| Headstrap: | Woven Elastic [Latex-Free] |
| Headstrap Adjuster: | Polypropylene |
| Exhalation Valve - Valve Housing: | Polypropylene & ABS |
| Valve Membrane: | Synthetic Rubber |

DIMENSIONS

| ITEM | LENGTH (mm) | WIDTH (mm) | HEIGHT (mm) | |
|---------------|----------------|---------------|----------------|--|
| Respirator | 155 | 70 | 125 | |
| Nosebridge | 25 | 50 | 35 | |
| Headband | 700 | 9 | 0.4 | |
| Headband clip | 57 | 12 | 9 | |
| Valve | 43 | 43 | 10 | |

CERTIFICATION

EU Certification according to Regulation (EU) 2016/425 issued by: BSI Group, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes, MK5 8PP, United Kingdom. [N.B. No.0086].

RECOMMENDATIONS FOR USE

This respirator is disposable and recommended for single shift use only.

Do not attempt to clean or re-use.

PRODUCT SELECTOR GUIDANCE CHART

| Approval EN 149: 2001 + A1:2009 | Mesh Colour | Product Codes | APF (Assigned Protection Factor) (x WEL) | Non-Toxic Dusts | Fine / Toxic Dusts / Mists / Fumes | VeryFine / Toxic Dusts / Mists / Fumes | Odours/ Organic Vapours (Below WEL) | Metal Fumes | Oil/Water Based Particulates |
|---------------------------------------|-------------|------------------|--|--------------------|---|--|--|----------------|------------------------------------|
| FFP1 NR | White | AMF-1 | 4 | | | | | | |
| FFP2 NR | Blue | AMF-2 | 10 | 0 | | | | 0 | |
| FFP2 NR | Blue | AMF-2V | 10 | 0 | | | | 0 | |
| FFP3 R D ◢ | Orange | AMF-3V | 20 | 0 | | | | 0 | |
| FFP3 NR 🗸 | Grey | AMF-3CV | 20 | 0 | | | | | |

www.alphasolway.com T: +44 (0)1461 202452 E: alphasolway.sales@globusgroup.com

ALPHA SOLWAY LTD, Factory 1, Queensberry Street, Annan, DG12 5BL, UK

ALPHA-DATA-AMF